

Installation

Turn your radio off before making these connections

Plug the BLUKIT into the CD changer input on the back of your Custom Autosound CD ready radio. If you are using a CD changer plug it into the 8 pin plug on the BLUKIT box.

Secure the box behind your dash.

The Bluetooth button and microphone need to be mounted in a location that is accessible. As an example the microphone may be mounted on the sun visor and the wire run down the a pillar to the Bluetooth button. This button must be accessible while driving. It is used to anser and hang up your cell phone calls. You may have to try different locations for the microphone to get the best sound quality.

8 Pin plug from the CD
changer if CD is used

8 Pin plug to CD
changer port on the
radio.



Bluetooth Button

Microphone

Bluetooth® Operation

BLUKIT OPERATION

Overview

Connecting a Bluetooth device requires first connecting the BLUKIT Bluetooth interface module. When connected to a Custom Autosound CD ready head unit, the BLUKIT supports the HFP (hands-free profile), A2DP (advanced audio distribution profile).

Preparation

Before you can use a mobile device with this head unit, it must be paired and connected. Please make sure that Bluetooth is activated on your mobile device before you begin the pairing process. Refer to the owner's manual of your mobile device for more details.

Bluetooth Pairing

- 1) To pair a Bluetooth enabled mobile phone to your head unit, put the head unit in CD mode
- 2) If the BLUKIT is connected properly the green Bluetooth button will be flashing.
- 3) Complete the pairing from the Bluetooth menu of your mobile device by searching for new devices. Please refer to your mobile device instructions for further information on Bluetooth pairing and connections. The Bluetooth light will illuminate solid when connected.

The BLUKIT device name is "CHB011."

The password for the BLUKIT is 0000. Not all phones require a password.

Compatibility

- Due to the differences in Bluetooth technology, some mobile devices may be incompatible or function improperly when used with the BLUKIT.

Switching between radio modes:

To listen to your Bluetooth enabled device the radio must be in CD mode.

If using a CD changer and you wish to switch between CD and Bluetooth follow the procedure for your model of radio.

USA-630 to switch between Bluetooth and CD press the CD/Mode button 5 times. Pressing the CD button 5 time again will switch back to the previous mode.

USA-66 to switch between Bluetooth and CD press the CD button 4 times rapidly to switch to bluetooth. Repeat the process to go back to CD changer.

Secretaudio to switch between Bluetooth and CD press the CD/Mode button 5 times. Pressing the CD button 5 time again will switch back to the previous mode.

Answering Phone: If your phone rings while in Bluetooth mode you will hear it through your stereo speakers. Just press the Bluetooth button to anser. When done with your call press again and your music will return. If you are in another mode when the phone rings put your radio into Bluetooth mode (CD mode) and press the Bluetooth button.

Music control:

If your phone is capable you can advance the song you are listening to by using the track up on your radio.

Bluetooth power off:

Once you turn the radio or ignition off the BLUKIT will delay off in 20 seconds. When you turn power back on your Bluetooth should reconnect automatically on most phones.

A large, light gray graphic consisting of several concentric, slightly irregular circular lines, similar to the sound wave graphic in the logo, is centered on the right side of the page. It serves as a background for the product title.

BLUKIT Bluetooth® Interface for Custom Autosound Radio models USA-630, USA-66, Secretaudio

Custom Autosound Mfg., Inc.
1030 W. Williamson Ave.
Fullerton, CA 92833
(714) 773-1423 (800) 888-8637
www.custom-autosound.com